

COMPACT SIZE. MANOEUVRABLE. 40 LITRES.
ALL IN ONE APPLIANCE.

RA 43|B 40
RA 55|B 40

- ❶ The universal scrubber dryer is available in various specifications – for multiple applications on all floors.
- ❷ Innovative lateral bumper rollers protect machine and other objects.
- ❸ Service-friendly: easy maintenance with open access to battery and components.
- ❹ Easy to operate without interruption of the working times with rugged mechanics instead of electronics: two functional switches on the handlebar, mechanical lowering of brush and squeegee tool.
- ❺ Infinite dosage: the right amount of fresh water for any application.
- ❻ Hygienic according to HACCP standards: the scrubber dryer features a removable recovery tank with an easy to replace cover gasket for thorough cleaning and disinfection – the only one in its class. Excess fresh water can be drained completely.



BACKWARDS AND FORWARDS: TRACTION MOTOR
WITH AUTOMATIC SPEED CONTROL.

RA 43|BM 40
RA 55|BM 40

- ❶ Intuitive, fatigue-free and safe working: height-adjustable handle bar, easy to operate control panel with ergonomic rocker function for back- and forward movements.
- ❷ Easy-to-read fresh water level indicator integrated into the drain hose.
- ❸ Standard splash guard for the brush head. Reduces water and chemical consumption and is eco-friendly.
- ❹ Optional features for customization: with/without traction motor, two different cleaning widths, with/without integrated battery charger, with/without chemicals supply system, battery capacity from 76 Ah 5 to 110 Ah 5.
- ❺ Optional silent version operates at a sound level of only 60 dB(A) for cleaning in sensible applications.



TWO WORKING WIDTHS.



	RA 43 B40	RA 55 B40
L x W x H	1140 x 510 x 870 mm	1200 x 550 x 870 mm
Working width	430 mm	550 mm
Suction width	730 mm	850 mm
Theoretical coverage max.	1720 m ² /h	2200 m ² /h
Noise level	65/60* dB(A)	65/60* dB(A)
Empty weight	75 kg	77 kg
Operating weight (105 Ah 5)	193 kg	195 kg

BATTERIES/ELECTRICAL DATA

Rated voltage	24 V	24 V
Power max.	900 W	900 W
Number of batteries	2	2
Capacity wet	110 Ah 5	110 Ah 5
Capacity gel	105 Ah 5	105 Ah 5

TANK

Solution tank capacity	40 l	40 l
Recovery tank capacity	40 l	40 l

SUCTION

Low pressure max.	110 mbar	110 mbar
Air flow max.	32 l/s	32 l/s

BRUSHES AND PAD HOLDERS

Number	1	1
Speed	150 rpm	150 rpm
Brush pressure	23 kg	24 kg

*silent version, optional.

TWO VARIATIONS.



	RA 43 BM40	RA 55 BM40
L x W x H	1140 x 510 x 870 mm	1200 x 550 x 870 mm
Working width	430 mm	550 mm
Suction width	730 mm	850 mm
Theoretical coverage max.	1720 m ² /h	2200 m ² /h
Noise level	65/60* dB(A)	65/60* dB(A)
Empty weight	82 kg	84 kg
Operating weight (105 Ah 5)	200 kg	202 kg

BATTERIES/ELECTRICAL DATA

Rated voltage	24 V	24 V
Power max.	1050 W	1050 W
Number of batteries	2	2
Capacity wet	110 Ah 5	110 Ah 5
Capacity gel	105 Ah 5	105 Ah 5

TANK

Solution tank capacity	40 l	40 l
Recovery tank capacity	40 l	40 l

SUCTION

Low pressure max.	110 mbar	110 mbar
Air flow max.	32 l/s	32 l/s

TRACTION

Power max.	150 W	150 W
Speed max.	4 km/h	4 km/h

BRUSHES AND PAD HOLDERS

Number	1	1
Speed	150 rpm	150 rpm
Brush pressure	23 kg	24 kg

*silent version, optional.